



## MATERIAL SAFETY DATA SHEET

### TECHNICAL SPECIFIED RUBBER

#### COMPANY IDENTIFICATION AND CHEMICAL PRODUCT

Material Name	TSR10, TSR20, TSR5, TSRL, TSR3L, TSR-CV50/60, RSS
Manufacturer	Factories in Asia and Africa
Intended for use	General purpose rubber articles.
Chemical Name / Family	Natural Rubber/Cis 1, 4 Poly Isoprene

#### HAZARDS IDENTIFICATION

Emergency Overview	No known OSHA hazards.
General Advice	This product is classified as “articles” and to not constitute a hazardous material in solid form under the definitions of the OSHA hazard communication Standard (29CFR1910.1200). Any articles manufactured from these solid products would be generally classified as non-hazardous.
Inhalation	May be harmful if inhaled. Seek medical advice.
Health Effects	May cause allergic reaction to persons with natural latex rubber Sensitivity.

#### COMPOSITION/ INGREDIENT INFORMATION

CAS #	9006 - 04 - 6
Chemical name	Cis 14 Polyisoprene
ACGIH TLV	Constant Viscosity (CV) Grades only. Grades not recommended for use with foodstuffs or pharmaceutical goods.



### FIRST AID MEASURES

Inhalation	May be harmful if swallowed seek medical advice.
Eyes	Irrigate with water.
Skin	Wash with warm water and mild soap.
Ingestion	May be harmful if swallowed. Seek medical advice.
General Advise	May cause allergic reaction to persons with natural latex rubber sensitivity. Handling of solid rubber is not a serious health hazard and does not require special first aid facilities. If in doubt, seek medical attention.

### FIRE FIGHTING MEASURES

Flammability	Yes		
Flammability conditions	Heat/Oxidation		
Extinction Means	Water sprinkler / foam, CO2 or dry chemical extinguishers		
Special Procedure	None		
Flash Point and Method	<b>Upper Explosion limit (% by Volume)</b>	<b>Lower Explosion limit (% by Volume)</b>	
> 300 C	Unknown	Unknown	
Auto Ignition Temperature	<b>TDG Flammability Classification</b>	<b>Hazardous combustion Product</b>	
> 300 C	Unknown	Carbon Monoxide	
Sensitivity to Chemical Impact	<b>Rate of Burning</b>	<b>Explosive Power</b>	<b>Sensitivity to Static Discharge</b>
Unknown	Varies	Unknown	Unknown



#### ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid ingestion, avoid inhalation of vapour or smoke from combustion.
Product Precautions	Normal methods for prevention of fire are required.
Personal Protection	Wear appropriate protective clothing, gloves and equipment.
Environmental Precautions	Ventilate if possible. Do not allow products to enter drains or water.

#### HANDLING AND STORAGE

Handling procedure & equipment	No special handling requirement
Storage Requirements	Keep out of direct sunlight, in a dry and ventilated area. Keep away from oxidation-catalysts.
Special shipping Information	None.
Waste Disposal	Keep in suitable container for disposal. Follow local laws for reclaim in needed.
Specific end use(s)	Rubber compound and Medical production.

#### EXPOSURE CONTROL AND PERSONAL PROTECTION

Personal Protective Equipment		Clothing when processing	
Gloves (specify)	Respiratory (specify)	Eyes (specify)	Footwear (specify)
Yes	Yes	Yes	Yes
Clothing (specify)	Other (specify)		
Yes	Protective clothing to prevent prolonged exposure to skin		



#### PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Solid
Odour	Slight
Appearance	Varied by grade
Odor Threshold	NA
Density (g/ml)	0.92
Vapor Pressure	NA
Vapor Density	NA
Evaporation Rate	NA
Initial Boiling Point	NA
Freezing Point	Glass transition at -70°C
Melting Point	Not applicable
Flash Point	> 300 °C
pH	NA
Flammability	Yes
Upper/Lower Flammable Limit	Unknown
Solubility	Carbon disulfide, chlorinated hydrocarbons
Partition Coefficient	NA
Auto-ignition Temperature	> 300 °C
Decomposition Temperature	NA
Viscosity	50 to 90 ML(1+4) at 100°C



#### STABILITY AND REACTIVITY

Chemical Stability	Yes, Product is in solid form.
Incompatibility to other products	Heavy Metals (Cu) acting as pre-oxidants.
Reactivity and under what conditions	Starts to decompose above 200°C, finally emitting vapours which may be toxic and flammable at temperatures near 300°C
Hazardous Decomposition Product	Isoprene derivations: carbon monoxide

#### TOXICOLOGY PROPERTIES OF PRODUCTS

Route of Entry	Ingestion
Effects of Acute Exposure to Product	Unknown, but avoid ingestion.
Effects of Chronic Exposure to Product	Unknown, but avoid ingestion.
LD50 Of Product (Route)	Unknown
Irritancy of Product	Unknown
Exposure Limit of Product	Unknown

#### ECOLOGICAL PROPERTIES OF PRODUCT

Potential for Ground Contamination	No major hazards to health. Product will biodegrade.
Potential for Water Contamination	Not hydroscopic. Exposure to water will cause mould.
Potential for Air Contamination	Ventilation not needed, strong odour fades with time.



#### WASTE DISPOSAL OF PRODUCT

Disposal Method	Dispose, incinerate or reclaim in accordance with local, regional and national environmental laws and regulations.
Special Procedures	None

#### TRANSPORT INFORMATION OF PRODUCT

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/AND)-Additional information	Not subject to ADR, RID and ADN
International Maritime Dangerous goods Code (IMDG)-Additional information	Not subject to IMDG
International Civil Aviation Organization (ICAO-IATA/DGR)-Additional information	Not subject to ICAO-IATA
DOT Classification	Not a DOT controlled material

#### REGULATORY INFORMATION

Product does not contain a SARA S-313 toxic chemicals above DE minimal thresholds.

Natural Rubber is NOT considered hazardous under OSHA hazard communication standard 29 CFR 1910.1200 or the WHMIS Canadian Legislation.

#### SOURCES USED

BRMA Toxicity and Safe Handling of Rubber Chemicals; British Rubber Manufacturers Associations. Health and Safety; Malaysian Natural Rubber.

#### OTHER INFORMATION

This data sheet is supplied to our customers as a courtesy. The information presented above has been gathered from what we consider reliable sources. While we believe it to be accurate and dependable, However, it is not guaranteed. It is the User responsibility to assess the suitability of the materials for their intended application. We cannot be held responsible for the functionality or use of such materials, as individual customer circumstances are beyond our control.